



## AXIS F1004 Sensor Unit

Super small size and price for discreet surveillance

AXIS F1004 Sensor Unit is small in size and price. For use with an AXIS F Main Unit, AXIS F1004 offers a lower cost, highly discreet sensor unit for indoor surveillance applications. AXIS F1004, which comprises a fixed lens and image sensor, provides a 720p resolution and a 102° horizontal field of view. AXIS F1004 has a detachable 8-m (26 ft.) cable for connecting to a main unit. A flush ceiling/wall mount kit is included. Optional accessories include surface and recessed mounts that enable the sensor unit to be tilted, and a 15-m (49 ft.) cable for connecting AXIS F1004 to a main unit.

- Small size and price
- 102° horizontal field of view
- HDTV 720p
- Detachable cable for easy and flexible installation

### Discreet surveillance

AXIS F1004 Sensor Unit is small in size and price. It offers a lower cost, highly discreet sensor unit for use with an AXIS F Main Unit. It is ideal for indoor surveillance of small stores and offices.

### Features

AXIS F1004, which comprises a fixed lens and image sensor, provides a 102° horizontal field of view and supports HDTV 720p video. The sensor unit comes with a detachable 8-m (26 ft.) cable for connection to an AXIS F Main Unit. The optional cable accessory, AXIS F7315 Cable White 15 m, is available if a longer cable connection is required between the sensor unit and the main unit. Included with AXIS F1004 is a flush mount kit for installing the sensor unit in walls or ceilings.



### Optional accessories

Optional accessories include the surface mount AXIS F8214 Dome Accessory and the recessed mount AXIS F8224. The optional mounts enable AXIS F1004 to be tilted to achieve the desired viewing direction when installed in or on ceilings and walls. When AXIS F8214 or AXIS F8224 is used, AXIS F1004 would be the smallest fixed dome and recessed dome offerings from Axis, measuring 7.4 cm (2 7/8 in.) in diameter.



# Axis F Series Mini HD CCTV Technology



## Specifications

### AXIS F1004 Sensor Unit

Camera		General	
Image sensor	1/4" (effective) progressive scan RGB CMOS	Casing	Zinc and plastic
Lens	Fixed iris 2.1 mm, F2.2 Horizontal angle of view: 102° Vertical angle of view: 56°	Operating conditions	-20 °C to 50 °C (-4 °F to 122 °F) Humidity 10–85% RH (non-condensing)
Resolutions	Max 1280x720	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F)
Wide dynamic range	WDR	Approvals	IEC/EN/UL 60950-1, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78, EN 55024, EN 61000-6-1, EN 61000-6-2, EN 61000-3-2, EN 61000-3-3, EN 50581, IEC 60529 IP3x, EN 55022 Class B, FCC Part 15 Subpart B Class B, ICES-003 Class B, VCCI Class B, RCM AS/NZS CISPR 22 Class B, KCC KN22 Class B, KN24
Minimum illumination	Color: 0.4 lux	Dimensions	37.5 mm (1 1/2 in) ø 16 mm (5/8 in)
Shutter time	1/24500 s to 1/6 s	Weight	96 g (0.21 lb)
Frame rate	Max 25/30 fps (50/60 Hz)	Required hardware	AXIS F Main Unit
		Included accessories	Installation Guide Flush mount kit for installation in wall or ceiling
		Optional accessories	AXIS F7315 Cable White 15 m AXIS F8214 Dome Accessory AXIS F8224 Recessed Mount AXIS F8204 Mounting band Mounting bracket for AXIS P1214/P1214-E/P1224-E
		Warranty	Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>